



April 11 1888
I commenced Survey of Section
11 Town 8 North,
Range 7 West.
W. W. Clagston
County Surveyor.

COURSE.	DISTANCE.	REMARKS.
		From S E
North	40.07	to E 1/4 4°36'
	82.15	to A E
		From S E
West	81.18	to S W 2°45'
		From S W
North	40.13	to W 1/4 3°32'
		From W 1/4
North	42.68	to A W 3°45'
		From A W
East	80.29	to A E 2°
		From S 1/4
North	40.18	to cen 1/4 4°10'
	82.42	to A 1/4
		From W 1/4
East	40.37	to cen 1/4 2°40'
	80.70	to E 1/4

Corners Established.	Monument.	Bearing Trees.	Diameter in Inches.	Course.	Links Distant.	Device on corner
Re Est S E	Stone	W Oak	30	A 57 N	72 1/2	33 34
		" "	30	A 18 1/2 N	119	
Re Est A W	Stone already set	B Oak	20	S 37 E	22	
		W Oak	20	A 86 E	19	
		Stone		S 88 E	24	being the SW cor of Sec 33-7-7
Re Est A E		W Oak	10	A 72 1/2 E	86	
		" "	18	A 23 E	118	
E 1/4	Stone	Hickory	20	S 67 1/2 E	109	43
		B Oak	15	S 41 E	101	
S 1/4 S E 1/4	Stone	W Oak	18	S 61 E	110 1/2	1/4 43
		" "	10	A 66 1/2 E	124 1/2	
S 1/4	Stone	W Oak	30	S 63 E	110	1/4 3
		" "	30	S 22 1/2 E	117	
A 1/4		W Oak	24	S 73 1/2 N	28 1/2	
			15	S 45 1/2 N	58	
Cen 1/4	Stone	Post Oak	8	S 26 N	36	
		Stone		North	50	
A 1/4 S E 1/4		Water Oak	20	A 36 E	64	
	Stone	" "	18	A 16 1/2 E	74	1/4 43
A 1/4 A W 1/4	Stone	B Oak	24	A 42 1/2 N	29	1/4 1/2 3
		Stone		East	19	being S 1/4 S W 1/4 Sec 19 33-7-7
5 chains west of cen of A W 1/4		B Oak	18	S 5 N	25 1/2	unmarked
Cen A W 1/4	Stone	Hickory	15	A 85 N	45	
		B Oak	12	A 34 1/2 E	124	
S 1/4 A W 1/4	Stone already set	NW Pillar under building		S 37 E	54	
S 1/4 S W	Stone	Stone		A 42 E	49	1/4 1/2 3
		"		A 35 1/2 N	50	
ch 668 3/4 S of W 1/4 S W	"	Cusimmon	8	A 79 N	23	
668 3/4 S of cen S W	"					
W 1/4 S W	"	Stone		East	27	1/4 1/2 3
		"		A 82 N	27	
Cen S W 1/4	"	Stone		S 85 1/2 N	31	1/4 1/2 3
		"		A 88 E	28 1/2	